

# BUNDED OIL TANKS Secure Storage

Harlequin®  
StorageTanks®

RELIABLE CONTAINERS

## Harlequin Bunded Oil Tanks

The Harlequin range of Bunded Oil Tanks are available from 650 litres, up to 9,250 litre models. Each tank has been designed and manufactured to exceed the most technical, environmental and regulatory requirements. Available as a tank only HQI model, tank and tankpack ITE model, or top outlet ITT model.

## What is a Bunded Oil Tank?

A 'Bunded' oil tank simply consists of a tank within a tank. Oil is stored in the inner tank and the outer tank acts as a failsafe so that in the event of a spillage, excess oil will collect in the outer tank - thus averting a pollution incident and costly environmental clean-up operation.

Bunded oil tanks have been proven to significantly reduce the risk of pollution at oil storage installations. They are a requirement at most commercial, industrial and institutional premises; all installations in the Channel Islands; and, at many domestic installations in the United Kingdom and Republic of Ireland.

## Benefits of a Harlequin Bunded Oil Tank:

- **More Options** - the full range has 15 options of tank size, a tank to suit every installation requirement.
- **Integrally Bunded** - designed to protect the surrounding environment, all tanks are bunded preventing pollution if the internal tank was ever to leak.
- **Non Corrosive** - manufactured from Medium Density Polyethylene (MDPE) your Harlequin tank will not corrode.
- **10 Year Guarantee** - peace of mind that should an issue arise with your tank, Harlequin will be there to help. \*10 year guarantee upon registration with Harlequin.
- **Meets Regulations** - as well as being fully bunded, each tank meets all relevant regulatory requirements.
- **Contents Monitoring** - each model has a 32mm hole suitable for fitting an electronic gauge. Gauge is standard with ITE and ITT models



All tanks are fully bunded and meet all regulatory requirements.

## ABOUT HARLEQUIN MFG

Being one of Europe's largest manufacturers of rotationally moulded plastic tanks, we've been at the forefront of product developments for over 35 years. From our base in Northern Ireland we design, manufacture and deliver our tanks all over the world.

With your Harlequin tank you can be assured you have the best solution for your needs. Our unrivalled reputation for quality is backed up by our 9001, 14001 and 18001 Management System Certifications.

Visit our website to find out about our full range of products:

Fuel/Diesel Tanks | Hot Water Storage | AdBlue Tanks | Water Tanks | Rainwater Harvesting | Sewage Treatment | Bunkers



Follow Us:  
@HarlequinMFG



For the latest product information, give us a call or visit our website:

T 028 9261 1077 E [Info@harlequin-mfg.com](mailto:Info@harlequin-mfg.com)  
[www.harlequinplastics.co.uk](http://www.harlequinplastics.co.uk)

Harlequin®  
MANUFACTURING FOR TOMORROW

# Bunded Oil Tanks

The Harlequin range of Bunded Oil Tanks are manufactured to exceed the most demanding technical, environmental and regulatory requirements. Available from 650 litres right up to 9,250 litre models, each tank is CE marked where appropriate with Declarations of Performance available on request.



**650 HQi / ITE / ITT**  
**SLIMLINE**  
Length 1,715mm  
Width 670mm  
Height 1,330mm  
Capacity 673 litres  
Weight 116kg

OFCERT License no: 0644051004R



**1000 HQi / ITE / ITT**  
**SLIMLINE**  
Length 2,150mm  
Width 690mm  
Height 1,420mm  
Capacity 1,055 litres  
Weight 132kg

OFCERT License no: 0644051005R



**1100 HQi / ITE / ITT**  
**SLIMLINE**  
Length 1,880mm  
Width 890mm  
Height 1,595mm  
Capacity 1,097 litres  
Weight 135kg

OFCERT License no: 0644010901R



**1200 HQi / ITE / ITT**  
**LOW PROFILE**  
Length 1,900mm  
Width 1,600mm  
Height 960mm  
Capacity 1,317 litres  
Weight 130kg

OFCERT License no: 0644031201



**1225 HQi / ITE / ITT**  
**SLIMLINE**  
Length 2,110mm  
Width 840mm  
Height 1,525mm  
Capacity 1,248 litres  
Weight 150kg

OFCERT License no: 0644081802



**1300 HQi / ITE / ITT**  
**SLIMLINE**  
Length 2,100mm  
Width 950mm  
Height 1,540mm  
Capacity 1,344 litres  
Weight 170kg

OFCERT License no: 0644051006R



**1400 HQi / ITE / ITT**  
**HORIZONTAL**  
Length 1,900mm  
Width 1,250mm  
Height 1,420mm  
Capacity 1,452 litres  
Weight 135kg

OFCERT License no: 0644010902R



**1450 HQi / ITE / ITT**  
**VERTICAL**  
Diameter 1,560mm  
Height 1,590mm  
Capacity 1,498 litres  
Weight 112kg

OFCERT License no: 0644010903R



**2000 HQi / ITE / ITT**  
**HORIZONTAL**  
Length 2,360mm  
Width 1,315mm  
Height 1,415mm  
Capacity 2,092 litres  
Weight 180kg

OFCERT License no: 0644010904R

**NEW**



**2500 HQi / ITE / ITT**  
**HORIZONTAL**  
Length 2,460mm  
Width 1,435mm  
Height 1,470mm  
Capacity 2,571 litres  
Weight 215kg

OFCERT License no: 0644051003R



**2525 HQi / ITE / ITT**  
**SLIMLINE**  
Length 2,450mm  
Width 1,200mm  
Height 1,685mm  
Capacity 2,550 litres  
Weight 235kg

OFCERT License: Pending



**3500 ITE / ITT**  
**HORIZONTAL**  
Length 2,450mm  
Width 1,770mm  
Height 1,890mm  
Capacity 3,471 litres  
Weight 275kg

OFCERT License no: 0644031202



**5400 ITE / ITT**  
**VERTICAL**  
Diameter 2,575mm  
Height 2,100mm  
Capacity 5,307 litres  
Weight 325kg

OFCERT License no: 0644010318R



**7500 ITE / ITT**  
**VERTICAL**  
Length 2,940mm  
Width 2,305mm  
Height 2,820mm  
Capacity 8,088 litres  
Weight 505kg

OFCERT License no: 0644121703



**9,250 ITE / ITT**  
**VERTICAL**  
Length 3,140mm  
Width 2,510mm  
Height 2,820mm  
Capacity 9,382 litres  
Weight 600kg

**OPTION 1: HQi**  
Bunded Oil Tank only.

Specification:

- Integrally bunded
- Bottom outlet with 1" BSP(F) thread
- 16" lockable access lid
- 4" lockable inspection cap (fill point for 350 model)
- 2" BSP(M) fill point (excludes 350 model)
- 32mm hole with cover for electronic gauge
- Inner tank vent (excludes 350 model)

Additional to specific models:

- Mechanical overfill prevention valve (3500, 5400, 7500 models)

**OPTION 2: ITE**  
Bunded Oil Tank with gauge and bottom outlet kit.

Specification:

- Integrally bunded
- Bottom outlet with 1" BSP(F) thread
- 16" lockable access lid
- 4" lockable inspection cap
- 2" BSP(M) fill point
- 32mm hole with cover for electronic gauge
- Inner tank vent
- Ultrasonic contents gauge with remote display
- Bottom outlet fitting kit
- LRC overfill prevention probe

Additional to 3500, 5400, 7500, 9250 models:

- Mechanical overfill prevention valve
- Bund Monitor

**OPTION 3: ITT**  
Bunded Oil Tank with top outlet & gauge.

Specification:

- Integrally bunded
- Tanktop top offtake fitting\*
- 16" lockable access lid
- 4" lockable inspection cap
- 2" BSP(M) fill point
- 32mm hole with cover for electronic gauge
- Inner tank vent
- Ultrasonic contents gauge with remote display
- LRC overfill prevention probe

Additional to 3500, 5400, 7500, 9250 models:

- Mechanical overfill prevention valve
- Bund Monitor

\* 5400, 7500, 9250 models fitted with Ecoflex top offtake fitting



Top Outlet

**Please Note:** All tank capacities are brimful. All OFCERT license numbers are for ITE models, ITT OFCERT license numbers are available on the OFTEC website. All information contained herein is understood to be correct at time of publication. Harlequin reserve the right to amend product specification without notice.

For the latest product information, give us a call or visit our website:

T 028 9261 1077 E [Info@harlequin-mfg.com](mailto:Info@harlequin-mfg.com)  
[www.harlequinplastics.co.uk](http://www.harlequinplastics.co.uk)

Your accredited Harlequin Reseller:



or contact us to find your nearest reseller: 028 9261 1077