



Bunded Oil Tanks: 16" Arag Lid Installation

Applicable to 350 Litre and 5400 Litre Harlequin Bunded Tanks

Step 1: Confirm correct fittings



Parts included are:

- 1 x 16" ARAG manhole lid (Lid top section may be green or red)
- 1 Vent connection and Hinge Pin
- 1.4m of paper backed Neoprene foam seal

Step 2: Assemble Lid Fittings



Ensure vent connection is screwed tightly onto underside of tank lid (may already be pre-fitted)



Knock the Hinge pin into the lid to secure the top section of the lid (may come pre-fitted)

You can also skip this step and fit hinge after attaching bottom section of lid to tank



Remove cover from Foam Seal Strip, cut to length and attach to underside of lid as shown

Step 3: Connect to Tank



Twist lid cap to separate top and bottom section of lid



Attach lid to tank using 8 self-tapping screws or rivets in assigned positions



Attach top half of lid using Hinge pin (if not already connected) and close lid by twisting lid spine until it lines up

Issued By:

Harlequin Manufacturing Limited, 21 Clarehill Road, Moira, Co. Armagh, N.Ireland, BT67 0PB

T: +44 (0)28 9261 1077

W: www.harlequin-mfg.com

E: info@harlequin-mfg.com